Congratulations on your purchase of the best filter on the market!
Your air filter is the lifeline to your engine... Improper maintenance can result in severe engine wear... Filter should be inspected every other oil change and cleaned and re-oiled every 30,000 miles under normal driving conditions. Under severe driving conditions or when engine is modified, filter should be serviced as needed.

Please read the following instructions carefully to achieve maximum engine protection and performance.

Installation Instructions

Your filter has been pre-treated with our specially designed tackifier and is ready for installation. When possible, before removing the filter from the plastic bag, massage in the tackifier so that the filter is `ed throughout. ***Excess tackifier must be removed from filter before installation.*** Blot using paper towels on front and backside of filter until excess tackifier is removed.

Make sure to install filter so that the airflow is entering the red side of the filter and exiting out the black side.

Cleaning Instructions

True Flow's Cleaning Kit (Part No. 95110)

True Flow Foam filter cleaner is necessary for proper cleaning!

True Flow Foam Filter Cleaner:
Spray generous amounts of True Flow Cleaner on the inside and outside of the filter. Let it soak approximately 15 minutes. Rinse out the filter element in warm water until clean.

For heavily soiled element, spray the filter thoroughly with cleaner and let the filter soak for 10 minutes. Then soak the filter in warm water for another 10 minutes. Filter may need to be agitated. Rinse out the filter element in warm water until clean.

Finally, make sure filter is completely dry before re-oiling. Tackifier will not adhere to filter if wet.

Now you're ready to apply tackifier.

DO NOT USE GAUZE OR COTTON OIL ON YOUR FOAM FILTER.

Application Instructions

True Flow Foam filter tackifier is necessary for proper filtration!

True Flow Filter Tackifier:
Spray the filter inside and out until the filter has complete coverage with the specially designed tackifier. Next work the tackifier into the foam using your hands. Repeat this step once more, and then dab filter with paper towels to remove excess tackifier. If your filter has a rubber mount flange, be sure to clean the mounting surface.

Clean filter frame, filter mounting surface and air box.

Now you're ready to install the best air filter on earth!

Limited Lifetime Warranty:
GCA Industries products are warranted to be free from material and workmanship defects for as long as the original purchaser owns the vehicle that the GCA Industries product was originally installed on (proof of purchase is required). This warranty is non-transferable. GCA Industries' limit of liability under this warranty is to repair or replace the product at GCA Industries' option. Consequential costs such as, but not limited to labor fees, loss of use, loss of time or freight charges are not covered. Any product that has been abused, altered, incorrectly installed or used in competition is not covered. Product finish is excluded from this warranty. Items that are subject to wear are not considered defective when worn and are not covered. No other warranties are expressed or implied. We reserve the right to make changes in design, materials and specifications without prior notice.

True Flow's foam filter has been treated with our specially designed foam tackifier. Cleaning or oiling filter with anything other than True Flow's cleaning kit will void warranty. Warranty will be voided if used for racing.